

Growatt GBLI3331 Lithium battery

- Compact size and easy installation
- High energy density and efficiency
- Excellent safety of LiFePO4 battery
- DoD up to 93%



P O W E R
- I N G O
T O M O -
R R O W O

Growatt
powering tomorrow

www.ginverter.com

Battery Data

Nominal Voltage	51.2V
Normal Capacity	3.3kWh
Usable Capacity	3kWh
Operating voltage	48 ~ 57.6V
Charging/Discharging Current	32A/42.5A
Rated discharging power	1.64KW
MAX discharging power	2.5KW/3s

General Data

Dimension (W/D/H)mm	444*131*394 (±1)
Weight	30Kg
IP Protection	IP20
Working temperature	-10°C~+50°C
Storage Temperature	-20°C~+45°C

Features

DoD	93%
Cycle Life	> 6000 (25°C, 90% DOD)
Parallel Connection	Max .6pack
Communication Port	CAN2.0 / RS485
Warranty	10 Years

IEC62619 , CE , UN38.3

* When the temperature is below 0 °C or above 45°C, the performance will be limited.

Growatt SPA1000~3000TL BL

- IP65 & Natural cooling
- Supports retrofit & New system
- Compatible with 1 & 3 phase system
- Workmodes programmable
- Online Smart Service



P O W E R
- I N G
T O M O R R O W
R R O W

Growatt
powering tomorrow

www.ginverter.com

Datasheet†	SPA1000TL BL	SPA2000TL BL	SPA3000TL BL
AC connection			
Rated AC apparent power	1000VA	2000VA	3000VA
Max. AC current	6A	10A	16A
AC nominal voltage (range)	230V (180V-270V)	230V (180V-270V)	230V (180V-270V)
AC grid frequency (range)	50Hz / 60Hz (±5Hz)	50Hz / 60Hz (±5Hz)	50Hz / 60Hz (±5Hz)
Power factor, configurable	1, 0.8leading...0.8lagging	1, 0.8leading...0.8lagging	1, 0.8leading...0.8lagging
THDi	<3%	<3%	<3%
AC connection	Single phase	Single phase	Single phase
AC output power (Back-up)			
Rated AC output apparent power	1000VA	2000VA	3000VA
Rated AC output voltage	230V	230V	230V
Rated AC output frequency	50Hz / 60Hz	50Hz / 60Hz	50Hz / 60Hz
Battery data			
Battery voltage range	42~59V	42~59V	42~59V
Max charging voltage	58V	58V	58V
Max charging and discharging current	24A	44A	66A
Peak charging and discharging power	1000W	2000W	3000W
Battery Type	Lithium /Lead-acid	Lithium /Lead-acid	Lithium /Lead-acid
Capacity of battery	50~2000AH	50~2000AH	50~2000AH
Efficiency			
Max. Charge efficiency	92.5%	94.0%	94.5%
Max. Discharge efficiency	92.0%	93.5%	94.0%
Protection devices			
Battery reverse protection	yes	yes	yes
Output over current protection	yes	yes	yes
Output over voltage protection-varistor	yes	yes	yes
Ground fault monitoring	yes	yes	yes
Grid monitoring	yes	yes	yes
Integrated all - pole sensitive leakage current monitoring unit	yes	yes	yes
General Data			
Dimensions (W / H / D) in mm	428/458/180	428/458/180	428/458/180
Weight	17kg	17kg	17kg
Operating temperature range	- 25°C ... +60°C	- 25°C ... +60°C	- 25°C ... +60°C
Noise emission (typical)	≤ 25 dB(A)	≤ 25 dB(A)	≤ 25 dB(A)
Altitude	2000m	2000m	2000m
Self-Consumption	<4W	<4W	<4W
Inverter Topology	transformerless	transformerless	transformerless
DC/DC topology	HF transformer	HF transformer	HF transformer
Cooling concept	Natural	Natural	Natural
Environmental Protection Rating	IP65	IP65	IP65
Relative humidity	100%	100%	100%
Features			
AC connection	connector	connector	connector
Battery connection	Screw	Screw	Screw
Display	LCD	LCD	LCD
Interfaces: RS485/ USB /CAN/WI-FI/RF	yes/yes/yes/opt/opt	yes/yes/yes/opt/opt	yes/yes/yes/opt/opt
Warranty:5 years/10 years	yes/opt	yes/opt	yes/opt

CE, IEC621109, G98, VDE0126-1-1, VDE-AR-N4105, CE 0-21, IEC62116&IEC61727, EN50438, AS4777, AS/NZS 3100